

ICOM

VHF MARINE TRANSCEIVER

IC-M25

New Style! Three Color Choices Smart Features



● Azul Marino



● Gris Metalico

● Blanco Perla



Alto rendimiento en una unidad delgada y liviana



Cargador USB (micro)



Bateria de 11 horas



LCD grande, Interface simple



Flota y Flashea



Parlante-microfono opcional, HM-213



Float'n Flash image

*For illustration purpose only

CARACTERISTICAS

Delgado, Liviano, Alta Capacidad

El IC-M25 tiene el cuerpo mas delgado (30.5mm; 1.2in) y liviano (220g; 7.8oz) de los transceiver (radios) marinos flotantes.

LCD Grande con interface simple

Con un LCD 30% mas grande que su predecesor el IC-M25's muestra claramente el canal de operacion y su estatus. Los botones al frente estan diseñados para una funcion simplificada.

Cargador USB (Tipo Micro-B USB)

Float'n Flash

El IC-M25 flota y te hace saber adonde esta flasheando su LED en color rojo la pantalla LED.

Parlante-microfono Opcional, HM-213

11 Horas de Bateria Continua

Con una bateria de 1500mAh litio-ion permite una operacion de 11 horas*.

* Typical operation with Tx (Hi): Rx: standby=5:5:90

El parlante-microfono HM-213 contra agua, provee grado comercial mientras es usado desde la cintura

550mW Audio Output

El IC-M25 provee una poderosa salida de audio de 550mW(tipica) que permite escuchar la voz fuerte y claro.

Otros

- Construcción contra agua IPX7
- Indicador de bateria de 4 estados
- Canal de estado del tiempo/alertas
- Funciones Dual/Tri-watch
- Acceso instantaneo a canal 16 o programable
- Funcion canal favorito
- Funcion de monitoreo permite apertura de squelch
- Funcion Auto-scan
- LCD iluminado
- AquaQuake™ funcion de drenaje de agua

ESPECIFICACIONES

GENERAL		
Frequency range	Tx Rx	156.025-157.425MHz 156.050-163.275MHz
Usable channel groups		INT, USA, CAN, WX channels
Type of emission		16K0G3E (FM)
Power supply voltage		3.7V DC nominal
Current drain	Tx Rx (Internal SP/External SP)	2.3A 300mA/200mA (Max. audio)
Operating temperature range		-20°C to +60°C; -4°F to +140°F
Antenna impedance		50Ω
Dimensions (WxHxD) (projections not included)		56.6x134.2x30.5mm; 2.2x5.3x1.2in
Weight (approximately)		220g; 7.8oz (With FA-SC59V and MB-133)

TRANSMITTER		
Output power		5W (approximately)/1W
Max. frequency deviation		±5.0kHz
Frequency stability		±10ppm
Spurious emissions		-68dBc typical
Adjacent channel power		70dB
Residual modulation		40dB
RECEIVER		
Sensitivity		0.25µV typical (at 12dB SINAD)
Squelch sensitivity		0.25µV typical (at threshold)
Adjacent channel selectivity		70dB typical
Spurious response		70dB typical
Intermodulation		70dB typical
Audio output power (at 10% distortion)	Internal SP	550mW typical (12Ω load)
	External SP	300mW typical (4Ω load)

Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.

Applicable IP Rating

Ingress Protection Standard	
Water	IPX7 (Waterproof protection)

Opcionales Consulte a su distribuidor por detalles



SA for USA, SE for Europe plug.



GENUINE The "3D GENUINE Icom label" is attached to the rear panel. Check the Icom website for details: <http://www.icom.co.jp/world/genuine-info/>

Icom, Icom Inc. and Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. AQUAQUAKE is a trademark of Icom Incorporated. All other products or brands are registered trademarks or trademarks of their respective holders.

Icom Inc. 1-1-32, Kami-minami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 www.icom.co.jp/world

Count on us!

Icom America Inc.
12421 Willows Road NE,
Kirkland, WA 98034, U.S.A.
Phone: +1 (425) 454-8155
Fax: +1 (425) 454-1509
E-mail: sales@icomamerica.com
URL: <http://www.icomamerica.com>

Icom Canada
Glenwood Centre #150-6165
Highway 17A, Delta, B.C.,
V4K 5B8, Canada
Phone: +1 (604) 952-4266
Fax: +1 (604) 952-0090
E-mail: info@icomcanada.com
URL: <http://www.icomcanada.com>

Icom Brazil
Rua Itororó, 444 Padre Eustáquio
Belo Horizonte MG,
CEP: 30720-450, Brazil
Phone: +55 (31) 3582 8847
Fax: +55 (31) 3582 8987
E-mail: sales@icombrazil.com

Icom (Europe) GmbH
Communication Equipment
Auf der Krautweide 24
65812 Bad Soden am Taunus, Germany
Phone: +49 (6196) 76685-0
Fax: +49 (6196) 76685-50
E-mail: info@icomeurope.com
URL: <http://www.icomeurope.com>

Icom Spain S.L.
Ctra. Rubí, No. 88 "Edificio Can Castanyer"
Bajos A 08174, Sant Cugat del Valles,
Barcelona, Spain
Phone: +34 (93) 590 26 70
Fax: +34 (93) 589 04 46
E-mail: info@icomspain.com
URL: <http://www.icomspain.com>

Icom (UK) Ltd.
Blacksole House, Altira Park,
Herne Bay, Kent, CT6 6GZ, U.K.
Phone: +44 (0) 1227 741741
Fax: +44 (0) 1227 741742
E-mail: info@icomuk.co.uk
URL: <http://www.icomuk.co.uk>

Icom France s.a.s.
Zac de la Plaine,
1 Rue Brindejonc des Moulinais, BP 45804,
31505 Toulouse Cedex 5, France
Phone: +33 (5) 61 36 03 03
Fax: +33 (5) 61 36 03 00
E-mail: icom@icom-france.com
URL: <http://www.icom-france.com>

Icom (Australia) Pty. Ltd.
Unit 1 / 103 Garden Road,
Clayton, VIC 3168 Australia
Phone: +61 (03) 9549 7500
Fax: +61 (03) 9549 7505
E-mail: sales@icom.net.au
URL: <http://www.icom.net.au>

Icom New Zealand
39C Rennis Drive, Airport Oaks,
Auckland, New Zealand
Phone: +64 (09) 274 4062
Fax: +64 (09) 274 4708
E-mail: inquiries@icom.co.nz
URL: <http://www.icom.co.nz>

Asia Icom Inc.
6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone: +886 (02) 2559 1899
Fax: +886 (02) 2559 1874
E-mail: sales@asia-icom.com
URL: <http://www.asia-icom.com>

Your local distributor/dealer:

REDICOM

Distribuidor Autorizado para Costa Rica
Telefono 2520-1616 email: info@redicom.cr
Direccion: Sabana Sur, 150 mts Oeste de la
Contraloria,
Edificio Edicol Piso 2, San Jose